

Wilson's Underlays can manufacture any underlay according to your specified requirements. For example, if a flame-retardant underlay is required for double-stick or EC Marine use, we can manufacture this as per your specification. Please ask a representative for more information.

Version 1.1 / Apr 2024

Flammability testing

Wilson's Underlays ensure that both extensive in house and external testing is carried out on our products we manufacture as well as testing to the BS4790:1987 standard. Where specified, our underlays are suitable for domestic and/or contract markets.

Technical specifications		
Flammability Testing	Result	Method
PU & Memory Foams	Low/Medium radius	BS4790:1987
Wool Blend	Low radius	BS4790:1987

What do the results mean?

The results were classified according to BS 5287:1988 (2014) 'Assessment and Labelling of Textile floorcoverings tested to BS 4790' The full descriptions of the classifications, abbreviated to **low**, **medium** or **high** in the table of results, are as follows:



LOW radius of effects of ignition (up to 35mm) / **MEDIUM** radius of effects of ignition (40 to 75mm) / **HIGH** radius of effects of ignition (80mm or over)



Manufactured by Wilson's Underlays Ltd, West Yorkshire, UK.
To view our full terms and conditions, visit wilsons-underlays.co.uk/terms-conditions.

01924 451 138 | sales@wilsons-group.com

wilsons-underlays.co.uk



Wilson's Underlays
THE BEST WAY TO TAKE CARE OF YOUR CARPETS