Multirich®







Superb thermal insulation from an underlay richly packed with wool fibres for a soft underfoot experience





17 - 37 dB (ΔLW)

Multirich®	28oz	42oz	56oz
Construction	Wool Felt	Wool Felt	Wool Felt
Density	28oz Sq. metre	42oz Sq. metre	56oz Sq. metre
Thickness	8mm	11mm	15mm
Tog Rating	1.2 TOG	3.4 TOG	3.6 TOG
Noise Reduction	17 dB (∆LW)	34 dB (∆LW)	37 dB (∆LW)
Comfort Rating	Average	Good	Luxury
Area Coverage	15m² (1.37m x 11m)	15m² (1.37m x 11m)	15m² (1.37m x 11m)
Roll Dimensions	140 x 35 x 35 cm	140 x 37 x 37 cm	140 x 40 x 40 cm
Double Stick Applications?	No	No	No
End Use Classification	Class GD/U General domestic use	Class HC/U Heavy contract use, suitable for heavy foot and wheel traffic and castor chairs	Class L/U Luxury use, domestic/contract, where high energy absorption is desirable





Product Specifications

Top Surface	Textured fibre appearance
Bottom Surface	Textured fibre appearance
Recyclable	Yes
Guarantee	Lifetime of initial carpet installation (when used in recommended areas)
Recommendation	Luxury domestic areas such as living rooms/bedrooms
Installation Method	Lay either fibre side upwards – the choice is yours. All corners must have spray adhesive applied. Always use a fresh, sharp blade/heavy duty shears when cutting.

Technical Specifications				
Testing	Result	Method		
Resistance to Cracking	<50mm	BS EN 14499:2015		
Static Loading	<40%	BS EN 14499:2015		
Dynamic Loading	<15%	BS EN 14499:2015		
Retention of Compression	>40%	BS EN 14499:2015		
Work of Compression	50-200J/m ²	BS EN 14499:2015		

Flammability Classification

Conforms to British Standards BS4790 flammability classification achieving a low radius result

Manufactured by Wilsons Underlays Ltd, West Yorkshire, UK. To view our full terms and conditions, visit wilsons-underlays.co.uk/terms-conditions

01924 451 138 | sales@wilsons-group.com



